

# 1045T-N

## Industrial surface mount magnetic contact

### Industrial Surface Mount Contact

---

The Sentrol 1045T series features a wider make distance, which permits faster installation, accommodates greater misalignment and works better on steel without time-consuming brackets. A wider break distance helps prevent false alarms caused by loose fitting doors. Sentrol-specified contacts keep the 1045 series from sticking or freezing on seldom-used doors.

### Applications

---

The contacts are used to protect openings such as metal entry/exit doors, overhead doors, roof hatches or hinged skylights.

### Durability and dependability

---

The Sentrol high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.



### Details

---

- Designed for commercial and industrial applications
- Can be used on steel without brackets
- Rugged construction
- Mounting screws
- Concealed terminals resist tampering and inadvertent shorting

# 1045T-N

## Industrial surface mount magnetic contact

National Sales Enquiries  
Level 4.01, 2 Ferntree Place Notting  
Hill, Victoria 3168  
Phone: 1300 361 479  
Outside Australia: +61 401 777 572  
[www.aritech.com.au](http://www.aritech.com.au)

### Technical specifications

#### Gap distance (max)

32 mm

#### Connections

Screw terminals

#### Contact

NC

#### Supervised loop

No

#### Dimensions (L x W x H)

99 x 15 x 18 mm

#### Color

White