

### B aritech

# EV1116 EV 1116AM

16m volumetric PIR motion sensor



#### **OVERVIEW**

Aritech motion sensors have the most advanced and sophisticated optics in the security industry. The EV1116 and EV1116AM are powerful 16m volumetric PIRs that feature the latest optical mirror technology of the 1000 series. To increase detection coverage, the 1000 series sensors use the 3Brid orthogonal curtain design. This is a horizontal mirror structure that produces curtains with vertical orientation to detect infrared. This orthogonal invention is the key in adding curtains to the mirror without sacrificing signal st ength, nor increasing the size of the sensor. The EV1116/AM produces 11 continuous curtains at 16m distance.

The EV1000AM series incorporates industry leading antimasking via active infrared technology. This advanced technology protects from the most advanced sabotage attempts including device penetration as well as wood, metals, ceramics, cardboard, paper, glass, PVC, spraypaint, lubricants and many other masking substances. The addition of dynamic pyro and circuitry diagnostics further ensure that the devices have not been tampered and are always in their correct operational state. PIRs of the 1000 series are the most rewarding sensors to install. They tolerate wall angle deviation and diffe ent mounting heights as well as limited loss of coverage when objects are placed in the field of vision. o make life easier no range setting is required thanks to constant range sensitivity while plug-in electronics make commissioning simple.

### **FEATURES**

- Passive Infrared motion sensor
- 3Brid Step & Gliding Focus Curtain mirror
- Plug-in electronics
- Sealed optics
- "5D" signal processing for false alarm immunity
- Cloak and umbrella immunity
- Full under crawl detection
- Selectable coverage pattern using mirror masks
- Auto focus with constant range sensitivity
- No adjustment required for diffe ent mounting heights
- Tolerates wall angle deviation
- Certified EN50131-2-2 G ade 2 & Grade 3



## EV1116/AM

16m volumetric PIR motion sensor

National Sales Enquiries Level 4.01, 2 Ferntree Place Notting Hill, Victoria 3168 Phone: 1300 361 479 Outside Australia: +61 401 777 572 www.aritech.com.au

### THE 1000 SERIES

The 1000 series are part of the Aritech's range of motion sensors. This family includes motion sensors with variants in housing size, detection range, anti-masking, dual detection technology, addressable interfacing, wireless transmission and more. This range covers all applications where security needs to be safeguarded. The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.

### **SPECIFICATIONS**

Detection range 16 m 16 m  Undercrawl protection Yes Yes  Sensitivity Normal / High Normal / High  Coverage field of view 86° with 11 curtains 86° with 11 curtains  Coverage pattern selection Curtain labels Curtain labels  Mounting height 1.8 to 3.0 m 1.8 to 3.0 m  Power supply 9 to 15 VDC 9 to 15 VDC  Current consumption (nom.) 4.4 mA 11 mA  Alarm relay (voltage free) NC when energised NC when energised  Tamper relay (voltage free) NC when cover closed  Remote control lines Walk test Walk test  Alarm memory Yes Yes  PIR signal processing 5D 5D  Dimensions (W x H x D) 125 x 65 x 60 mm			
Undercrawl protection Yes Yes Sensitivity Normal / High Normal / High Coverage field of view 86° with 11 curtains 86° with 11 curtains Coverage pattern selection Curtain labels Curtain labels Mounting height 1.8 to 3.0 m 1.8 to 3.0 m Power supply 9 to 15 VDC 9 to 15 VDC Current consumption (nom.) 4.4 mA 11 mA Alarm relay (voltage free) NC when energised NC when energised Tamper relay (voltage free) NC when cover closed Remote control lines Walk test Walk test Alarm memory Yes Yes PIR signal processing 5D 5D		EV1116	EV1116AM
Sensitivity  Normal / High  Normal / High  Coverage field of view  86° with 11 curtains  Coverage pattern selection  Curtain labels  Curtain labels  Mounting height  1.8 to 3.0 m  Power supply  9 to 15 VDC  9 to 15 VDC  Current consumption (nom.)  4.4 mA  Alarm relay (voltage free)  NC when energised  Tamper relay (voltage free)  NC when cover closed  Remote control lines  Walk test  Alarm memory  Yes  PIR signal processing  So with 11 curtains  86° with 11 curtains  Curtain labels  Late 3.0 m  9 to 15 VDC  9 to 15 VDC  9 to 15 VDC  Verent consumption (nom.)  4.4 mA  11 mA  NC when energised  NC when cover closed  NC when cover closed  So S	Detection range	16 m	16 m
Coverage field of view 86° with 11 curtains 86° with 11 curtains  Coverage pattern selection Curtain labels Curtain labels  Mounting height 1.8 to 3.0 m 1.8 to 3.0 m  Power supply 9 to 15 VDC 9 to 15 VDC  Current consumption (nom.) 4.4 mA 11 mA  Alarm relay (voltage free) NC when energised NC when energised  Tamper relay (voltage free) NC when cover closed  Remote control lines Walk test Walk test  Alarm memory Yes Yes  PIR signal processing 5D 5D	Undercrawl protection	Yes	Yes
Coverage pattern selection Curtain labels Curtain labels  Mounting height 1.8 to 3.0 m 1.8 to 3.0 m  Power supply 9 to 15 VDC 9 to 15 VDC  Current consumption (nom.) 4.4 mA 11 mA  Alarm relay (voltage free) NC when energised NC when energised  Tamper relay (voltage free) NC when cover closed NC when cover closed  Remote control lines Walk test Walk test  Alarm memory Yes Yes  PIR signal processing 5D 5D	Sensitivity	Normal / High	Normal / High
Mounting height 1.8 to 3.0 m 1.8 to 3.0 m  Power supply 9 to 15 VDC 9 to 15 VDC  Current consumption (nom.) 4.4 mA 11 mA  Alarm relay (voltage free) NC when energised NC when energised  Tamper relay (voltage free) NC when cover closed NC when cover closed  Remote control lines Walk test Walk test  Alarm memory Yes Yes  PIR signal processing 5D 5D	Coverage field of view	86° with 11 curtains	86° with 11 curtains
Power supply 9 to 15 VDC 9 to 15 VDC  Current consumption (nom.) 4.4 mA 11 mA  Alarm relay (voltage free) NC when energised NC when energised  Tamper relay (voltage free) NC when cover closed NC when cover closed  Remote control lines Walk test Walk test  Alarm memory Yes Yes  PIR signal processing 5D 5D	Coverage pattern selection	Curtain labels	Curtain labels
Current consumption (nom.) 4.4 mA 11 mA  Alarm relay (voltage free) NC when energised NC when energised  Tamper relay (voltage free) NC when cover closed NC when cover closed  Remote control lines Walk test Walk test  Alarm memory Yes Yes  PIR signal processing 5D 5D	Mounting height	1.8 to 3.0 m	1.8 to 3.0 m
Alarm relay (voltage free) NC when energised NC when energised Tamper relay (voltage free) NC when cover closed NC when cover closed Remote control lines Walk test Walk test Alarm memory Yes Yes PIR signal processing 5D 5D	Power supply	9 to 15 VDC	9 to 15 VDC
Tamper relay (voltage free)NC when cover closedNC when cover closedRemote control linesWalk testWalk testAlarm memoryYesYesPIR signal processing5D5D	Current consumption (nom.)	4.4 mA	11 mA
Remote control lines Walk test Walk test Alarm memory Yes Yes PIR signal processing 5D 5D	Alarm relay (voltage free)	NC when energised	NC when energised
Alarm memory Yes Yes PIR signal processing 5D 5D	Tamper relay (voltage free)	NC when cover closed	NC when cover closed
PIR signal processing 5D 5D	Remote control lines	Walk test	Walk test
	Alarm memory	Yes	Yes
Dimensions (W v H v D) 125 v 65 v 60 mm 125 v 65 v 60 mm	PIR signal processing	5D	5D
	Dimensions (W x H x D)	125 x 65 x 60 mm	125 x 65 x 60 mm
Ambient conditions -10 to +55°C -10 to +55°C	Ambient conditions	-10 to +55°C	-10 to +55°C
95% relative humidity 95% relative humidity		95% relative humidity	95% relative humidity
Pry-off tamper Optional (ST400) On board	Pry-off tamper	Optional (ST400)	On board
EN50131-2-2 Grade 2 Grade 3	EN50131-2-2	Grade 2	Grade 3



### ORDERING INFORMATION

EV1116	16m volumetric motion detector with 11 curtains, DSP
EV1116AM	16m volumetric motion detector with 11 curtains and anti-masking, DSP
EV1116AMZ	16m volumetric motion detector with 11 curtains and anti-masking, DSP, no alarm memory and no NC relay
SB01	Wall/ceiling mount bracket (± 45° horizontal, 0° or -5° vertical)
ST400	Pry-off Tamper Kit



