

## DC124 Contact

The DC107/124/125/887/888 contacts are designed specifically for use in steel doors commonly found in commercial building applications. Many models including, wide gap, CO and biased for high security applications make the series the most widely used and comprehensive line available.

### Easy Installation

The unique housing design features a rugged unibody construction with flexible ribbed sides for quick, secure installation without gluing. The magnet housing isolates the magnet from the surrounding steel for maximum gap distances, both make and break.



### Details

- Special design for steel mounting
- Self-lock mounting
- Comprehensive product range
- Standard 2 m wire length
- Tamper loop provided
- Built-in resistors available to special order

# DC124

## Contact

National Sales Enquiries  
Level 4.01, 2 Ferntree Place  
Notting Hill, Victoria 3168  
Phone: 1300 361 479  
Outside Australia: +61 401 777 572  
www.aritech.com.au

### Technical specifications

---

#### General

Application type	Recessed mount
Contact type	CO
Connectivity	5 wires, 2 m

#### Wired / wireless

Wired-wireless	Wired
Operating gap	9 mm (max.)

#### Physical

Dimensions magnet	24.1 x 39.7 mm (Ø x L)
Dimensions contact / sensor	24.1 x 29.5 mm (Ø x L)
Borehole diameter	19.1 mm
Colour	White

#### Regulatory

EN50131 grade	Grade 2
---------------	---------

